



Technical Specifications **MARK/CUT SLICE® Model 135-P/HS**

Model 135-P/ HS for hot stamp marking & cutting tubing

Standard accuracy: ± 1 mm

Typical standard deviation: 0.5 mm (.02")

Statistical data taken for 25 wires 11" long. Measurement data and a certification of calibration accompanies each unit when it is shipped.

Machine resolution: 0.5 mm (.02")

Process material at 20" per second

Will cut up to 10,000 4" pieces of product per hour cuts 4,800 10" pieces per hour

Hot Stamp Technology system's printing time is variable; actual pieces per hour may vary.

Print Area: 3.0" (76 mm) wide X 3.0" (76mm) long

High, repeatable accuracy

Vertical and horizontal adjustments

Digital electronic controls with stepper motor ribbon advance

Meets Mil Spec MIL-M-81531(AS)

Compatible with Kingsley type holders

Capabilities: Handles printing and cutting of heat shrink and other soft tubing, including reeled adhesive-lined heat shrink. It also cuts up to 60 conductor flat ribbon cable with precision.

99 batch programs in memory

30 batch file programs, each one consisting of up to 10 standard programs

Remembers place in batch program if power is lost.

Blade: Guillotine-type custom-designed blade and die set made of hardened tool steel,
58-60 Rockwell C

Air Supply, Hot Stamp and Slice 135:	90psi/6bar, clean and dry
Power requirements:	115/230 Volts 50/60 cycles
Environmental:	10 - 35 Degrees C
Hot Stamp Temperature:	150 to 400 F

Overall Physical Dimensions:

Length = 43 in.(excluding reel) Width = 21.5 in. Height = 33.5 in. Weight = 100 lb.

FCC Class B Certification

Patents Pending **SLICE®** is a registered trademark of AMTI. All rights reserved.

AMTI

Division of Maxant

7540 Caldwell Ave. Niles, IL 60714

Tel. 847 588 2280 Fax. 847 588 1920

slice@amti-products.com

www.amti-products.com